



HYMME / STOR

EN 13240:2001 & 13240 A2:2004

Met vaste brandstof gestookte ruimteverwarming
Roomheater fired by solid fuel capable of intermittent operation
Espace chauffé avec un combustible solides
Kaminofen für feste Brennstoffe

Afstand tot brandbare materialen; zij-, achterkant	10 cm, 10 cm (min)
Distance to adjacent combustible materials; side, back	
Espace depuis les matériaux inflammables; côté, arrière	
Abstand bis brennbarer Materialien; seite, hinter	

ECO Design emissie in verbrand product	CO	≤ 1500 mg/m ³
Emission ECO Design in combustion products	PM	≤ 40 mg/m ³
ECO Design émission dans les produits de combustion	OGC	≤ 120 mg/m ³
ECO Design Emission in verbranntes Produkt	NOx	≤ 200 mg/m ³

Rookgastemperatuur	218 °C
Flue gas temperature	
Température des fumées	
Abgastemperatur	

Vermogen	9.9 kW
Thermal output	
Puissance	
Nennwärmeleistung	

Rendement	≥ 75%
Energy efficiency	
Rendement	
Wirkungsgrad	

Brandstoftypes	Hout
Fuel types	Wood
Types de carburant	Bois
Zulassige Brennstoffe	Holz

Gebruik alleen aanbevolen brandstoffen! Lees en volg de instructies!
Use only recommended fuels! Read and follow the operating instructions!
Utilisez un combustible approprié! Lire et suivre les notices d'instructions!
Brauch nur empfohlen Brennstoffe! Anleitung beachten!